

Features

- Complete wireless socket meter package compatible with E-Mon D-Mon wireless metering solutions.
- Meter Features:
 - Electronic LCD Display
 - Polycarbonate Cover
 - Demand Reset
 - Optical Tower
 - Test Mode Push Button
 - Test LED
 - Meets ANSI, IEC and FCC standards.
 - Available Configurations:
 - Two or Three Wire
 - 120 or 240 Volt
 - Form 1S, 2S, 3S, 4S or 12S
 - Class 20, 100, 200 or 320
 - Temperature -40 to +85 degrees C.
 - Humidity 0% to 95% non-condensing
 - ANSI C12.20 0.5 Accuracy Class
- Wireless Features:
 - Operates in 915 MHz license-free bands
 - Installed "under the glass"
 - Fully self-configuring wireless mesh network
 - Automatic time synchronization
 - Local non-volatile data storage
 - Internal and external antenna options
 - Provides real-time access to interval data
 - Provides full wireless routing capability
 - Full peer-to-peer communication
 - Multiple redundant paths
 - No network address management required
 - Automatic network acquisition at Power ON
 - Automatic time synchronization of all meters in the network.



Dim: 6.29" Diameter x 4.98" Depth

Metering Packages

Multi-Family Residential

Voltage	Element	Form	Model
120/240V	1	2S	EMON2S
120/208V	2	12S	EMON12S

Three-Phase Commercial

Contact Factory at (800) 334-3666.

Additional Components

Wireless Gateway	WGATEWAY
Wireless Meter	
Reading Software	WRSOFT